Revision Date: July 17, 2023 Revision Number: 1

# SAFETY DATA SHEET

# 1. Identification of the substance/mixture and of the company

### 1.1 Product identifier

# Product Name: BonDuit® Gel Resin BT (Part A)

Product ID numbers: BT-KIT, BT-KITG, BT-KITB6, BT-KITB6G, BT-CART12PK

BT-XXX (where XXX is the package code.)

# 1.2 Relevant identified uses of the mixture and uses advised against

**Identified uses:** Sealant/adhesive resin, Part A of 2-Part Adhesive

**List of advices against:** Not applicable.

# 1.3 Details of the supplier of the safety data sheet

Supplier/Manufacturer:

American Polywater Corporation The Energy Network Pty LTD (Ten Group)

11222 - 60th Street North 65 Wentworth Place,

Stillwater, MN 55082 USA Banyo, Queensland 4014, Australia

Tel: 1-651-430-2270 (07) 3212 8999

Email: sds@polywater.com Email: sales@tengroup.com.au

### 1.4 Emergency telephone numbers

INFOTRAC: 1-800-535-5053 1-352-323-3500

NPC (National Poison Centre) 0800 764 766 and 0800 Poison

# 2. Hazards Identification

### 2.1 Classification of the substance or mixture

Classification according to USA OSHA 29 CFR 1910.1200 (2012) and Canada HPR (SOR/2015-17; WHMIS 2015).

| Skin Irritation, Category 2                                     | H315 |
|---|------|
| Skin Sensitization, Category 1                                  | H317 |
| Eye Irritation, Category 2                                      | H319 |
| Hazardous to the aquatic environment—Chronic Hazard, Category 2 | H411 |

### 2.2 Label elements

Contains: Bisphenol A-epichlorohydrin polymer





Pictograms:

GHS07 GHS09

Signal word: Warning

**Hazard Statements:** 

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H411 Toxic to aquatic life with long lasting effects.

**Precautionary Statements:** 

P261 Avoid breathing mist, vapours.

P264 Wash hands thoroughly after handling.

Product Name: BonDuit® Gel Resin (Part A) Type BT Revision Date: July 17, 2023

P272 Contaminated work clothing should not be allowed out of the workplace.

P273 Avoid release to the environment.

P280 Wear protective gloves, protective clothing and eye protection.

P302 + P352 IF ON SKIN: Wash with plenty of soap and water.
P333 + P313 If skin irritation or rash occurs: Get medical attention.

P305 + P351 + IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses

P338 if present and easy to do. Continue rinsing.
P337 + P313 If eye irritation persists: Get medical attention.

P362 + P364 Take off contaminated clothing.

P391 Collect spillage.

P501 Dispose of container in accordance with local regulations

**2.3 Other hazards:** No information available.

# 3. Composition/Information on Ingredients

Classification according to Regulation (EC) No. 1272/2008

Component Product identifier Weight % [CLP]

Bisphenol A-epichlorohydrin polymer (CAS-No.) 25068-38-6 75 – 90 Eye Irrit. 2, H319 Skin Irrit. 2, H315 (EC Index-No.) 603-074-00-8 Skin Sens. 1, H317 Aquatic Chronic 2, H411

This product contains no other reportable hazardous components under OSHA 29 CFR 1910, 1200 Canada and European Regulation (EC) No 1272/2008. No additional ingredients require reporting based on applicable concentration and current supplier knowledge.

### 4. First Aid Measures

# 4.1 Description of first aid measures

Eye Contact: Immediately flush eyes with large quantity of water for 15 minutes. Seek medical

attention.

Skin Contact: Remove contaminated clothing; flush skin thoroughly with soap and water for at

least 15 minutes. If irritation or allergic reaction occurs, seek medical attention.

Inhalation (Breathing): If irritation of nose or throat develops, move to fresh air. If irritation persists, seek

medical attention.

Ingestion (Swallowing): No emergency medical treatment necessary

### 4.2 Most important symptoms and effects, both acute and delayed

Refer to Section 11 for more information.

### 4.3 Indication of immediate medical attention and special treatment needed.

No information available.

# 5. Firefighting Measures

### 5.1 Extinguishing media:

Water fog or fine spray, dry chemical carbon dioxide, or foam.

### 5.2 Special hazards arising from the substance or mixture

Dense smoke is emitted when burned without sufficient oxygen.

# Hazardous decomposition and by-products:

CO<sub>2</sub>, CO, phenolics. May contain other combustion products of varying composition which may be toxic or irritating.

# 5.3 Advice for firefighters

Wear full protective clothing, including self-contained, positive pressure or pressure-demand breathing apparatus. Sealed container can build up pressure when exposed to high heat. Water fog may be used to

Product Name: BonDuit® Gel Resin (Part A) Type BT

cool fire exposed container to prevent pressure build-up and possible auto-ignition or rupture. Direct water stream may spread fire.

### 5.4 Hazchem code

None allocated.

### 6. Accidental Release Measures

# 6.1 Personal precautions, protective equipment and emergency procedures:

Isolate area. Use appropriate safety equipment.

### 6.2 Environmental precautions:

Avoid release to the environment. Prevent spill from entering drainage/sewer systems, waterways, basements or confined areas. Refer to Section 12 for more information.

# 6.3 Methods materials for containment and cleaning up:

Absorb spill with sand or absorbents. Residual resin may be removed using steam or hot soapy water. Collect as much of the spilled material as possible using non-sparking tools and transfer to a container. Seal the container. Residual material can be removed with solvent.

### 6.4 Reference to other sections:

Refer to Sections 4, 5, 8, and 13 for more information.

# 7. Handling and Storage

### 7.1 Precautions for safe handling

Avoid personal contact with the product. All containers should be disposed of in an environmentally safe manner and in accordance with governmental regulations. Wash thoroughly after handling. Wash contaminated clothing before reuse. For industrial or professional use only.

# 7.2 Conditions for safe storage, including incompatibilities

Keep containers cool, dry, and away from sources of ignition. Keep containers and cartridges capped and sealed. Protect from freezing. All containers should be disposed of in an environmentally safe manner and in accordance with governmental regulations.

### 7.3 Specific end uses

See technical data sheet on this product for further information.

# 8. Exposure Controls / Personal Protection

# 8.1 Control parameters

### **Exposure limits and recommendations:**

Contains no components with established Occupational Exposure Limit (OEL) values. A Derived No Effect Level (DNEL) of 12.25 mg/m³ has been established for Acute Inhalation.

### A Derived No Effect Level (DNEL) of 12.25 mg/m² has been established for Acute Inna

### 8.2 Exposure controls

# Respiratory protection:

Normal ventilation is adequate. If exposure exceeds recommended limits, respirator protection is recommended. Wear respiratory protection when adverse effects, such as respiratory irritation or discomfort have been experienced. Use a respirator or gas mask with cartridges for organic vapors (NIOSH or CE approved) with particulate pre-filter, P100 or AP2.

# Protective gloves:

The use of chemically resistant gloves is recommended to prevent skin contact. Suitable materials include nitrile (included in most kits), neoprene, ethyl vinyl alcohol (EVAL), PVC. Use a glove with a protection class of 1 or higher (breakthrough time greater than 10 minutes according to EN 374). NOTE: The selection of specific glove for the application should account for other chemicals in the environment, physical requirements and potential user reaction to the glove material.

# Eye protection:

Safety glasses recommended.

### Other protective equipment:

Revision Date: July 17, 2023

Product Name: BonDuit® Gel Resin (Part A) Type BT

Use protective cream if skin contact is likely. Remove and wash contaminated clothing before reuse. Discard contaminated shoes.

Revision Date: July 17, 2023

### Personal protective equipment symbol(s):





# 9. Physical and Chemical

# 9.1 Information of basic physical and chemical properties

**Appearance:** Dark gray or black gel.

Odor threshold:

pH:

Does not apply

Freezing point:

Not available

Not available

Not available

Not available

Flash point:

Evaporation rate:

Flammability (solid, gas):

Not available

Not available

Upper/lower flammability or

**explosive limits:** Not available

Vapor pressure: < 0.001 mm Hg @ 20°C

Vapor density (Air = 1): >1

Specific gravity (H₂O = 1): 1.2 @ 25°C Solubility in water: Not available

Partition coefficient: n-

octanol/water:Not availableAuto-ignition temperature:Not availableDecomposition temperature:Not availableViscosity:Not available

9.2 Other Information

Volatiles (Weight %): 0%
VOC Content: 0 g/l

# 10. Stability and Reactivity

### 10.1 Reactivity:

No dangerous reaction known under conditions of normal use.

# 10.2 Chemical stability:

Stable

### 10.3 Possibility of hazardous reactions:

Hazardous reactions will not occur under normal transport or storage conditions.

#### 10.4 Conditions to avoid:

Avoid high temperatures above 300 °C (572 °F). Decomposition can occur above 350 °C (662 °F). Generation of gas during decomposition can cause pressure to build in closed systems.

#### 10.5 Incompatible materials:

Strong acids or bases (especially primary or secondary aliphatic amines), strong oxidizing agents.

# 10.6 Hazardous decomposition products:

Product Name: BonDuit® Gel Resin (Part A) Type BT

CO<sub>2</sub>, CO, phenolics and other organic substances may be formed during combustion or elevated temperature degradation.

# 11. Toxicological Information

# 11.1 Information on toxicological effects:

# **Acute toxicity**

### Eye contact:

Direct eye contact with material or vapors may cause eye irritation.

#### Skin contact:

This product has moderate skin irritation potential. Persons with pre-existing skin disorders may be more susceptible to skin irritation from this material. Prolonged or repeated skin exposure may cause skin sensitization.

### Irritation and Sensitization Potential:

May cause allergic skin reaction.

### Inhalation (Breathing):

Low vapor pressure makes this route of exposure unlikely.

### Ingestion:

Ingestion may cause irritation of the gastrointestinal tract.

# **Toxicity to Animals:**

Bisphenol A Diglycidyl Ether: LD<sub>50</sub> (oral rat) >15,000 mg/kg

LD<sub>50</sub> (dermal rabbit) 23,000 mg/kg

# **Aspiration Hazard:**

No aspiration hazard expected.

### **Chronic Exposure:**

**Reproductive Toxicity:** Not available.

Resins based on diglycidyl ether of bisphenol A have proved to be inactive when tested by in-vivo mutagenicity assays. These resins have shown activity in in-vitro microbial mutagenicity screening and have produced chromosomal

Revision Date: July 17, 2023

aberrations in cultured rat-liver cells. The significance of these tests to

**Mutagenicity:** humans is unknown.

Teratogenicity:

**Specific Target Organ** 

**Toxicity (STOT)** Not available.

**Toxicologically Synergistic** 

**Products:** Not available.

Carcinogenic Status: This substance has not been identified as a carcinogen or probable

carcinogen by NTP, IARC, or OSHA, nor have any of its components.

# 12. Ecological Information

# 12.1 Toxicity:

**Aquatic Toxicity:** May be toxic to aquatic organisms.

Not available.

Bisphenol A Diglycidyl LC<sub>50</sub> (96 hr.): 2 mg/l Oncorhynchus mykiss (rainbow trout)

Ether: Semi-static test

Bisphenol A Diglycidyl EC<sub>50</sub> (48 hr.): 1.8 mg/l Daphnia magna (invertebrate)

Ether: Static test

Bisphenol A Diglycidyl ErC<sub>50</sub> (72 hr.): 11 mg/l Fresh water algae (aquatic plants)

Ether: Static test

Chronic Toxicity Value:

Bisphenol A Diglycidyl Daphnia magna (invertebrate),21 d, number of offspring, NOEC: 0.3 mg/l

Ether: Semi-static test

Product Name: BonDuit® Gel Resin (Part A) Type BT Revision Date: July 17, 2023

12.2 Persistence and Based on stringent OECD test guidelines, this material cannot be degradability:

considered readily biodegradable. Biodegradability depends on

environmental conditions.

Bisphenol A Diglycidyl OECD Biodegradation Test 302B 12% Biodegradation, 28 d exposure Ether:

Bisphenol A Diglycidyl Theoretical Oxygen Demand

Ether: 2.35 mg/mg

12.3 Bioaccumulation

potential: Bioconcentration potential is moderate. Potential for mobility in soil is low.. 12.4 Mobility in soil:

12.5 Results of PBT and

vPvB Assessment: This product is not, nor does it contain a substance that is a PBT or vPvB.

12.6 Other adverse effects: None known.

# 13. Disposal Considerations

Do not dump into sewer, on ground or into any body of water. Dispose of product in accordance with National and Local Regulations.

### 14. Transport Information

DOT: Not Regulated

**UN Number:** 3082

**UN Proper Shipping Name:** Environmentally hazardous substance, liquid, N.O.S. (Bisphenol A)

Class and Subsidiary Risk: **Packing Group:** Ш

ICAO/IATA-DGR: Not Regulated (See Special Provision A197) Not Regulated (See IMDG Code 2.10.2.7) IMDG:

ADR/RID:

Other information For surface shipments within the United States: Not regulated.

Hazchem code: None allocated

### 15. Regulatory Information

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

### 15.1.1. NZ-Regulations

All chemical substances in this product are listed in the New Zealand Inventory of Chemicals (NZIoC) or are exempt

This substance is to be managed using the conditions specified in an applicable Group Standard **HSR Number** 

HSR002544 Construction Products Group Standard

### 15.1.2. EU-regulations

- Contains no REACH substances with Annex XVII restrictions
- Contains no substance on the REACH candidate list
- Contains no REACH Annex XIV substances
- Contains no substance subject to REGULATION (EU) No 649/2012 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 4 July 2012 concerning the export and import of hazardous chemicals.
- Contains no substance subject to Regulation (EU) No 2019/1021 of the European Parliament and of the Council of 20 June 2019 on persistent organic pollutants.

# 15.1.3. Australian-regulations

Classified as a Schedule 5 (S5) Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP).

Product Name: BonDuit® Gel Resin (Part A) Type BT Revision Date: July 17, 2023

Safework Australia criteria is based on the Globally Harmonized System (GHS) of Classification and Labelling of Chemicals.

All components are listed on the AICS.

Product is classified as hazardous according to criteria of NOHSC Australia.

# 15.1.4. International-regulations

All chemical substances in this product are listed as "Active" in the US EPA (Environmental Protection Agency) "TSCA Inventory Notification (Active-Inactive) Requirements Rule" ("the Final Rule"). as of Feb. 2019 or are otherwise exempt.

### 15.2 Chemical Safety Assessment

No chemical safety assessment has been carried out for the mixture by the supplier.

### 16. Other Information

# Abbreviations and acronyms:

OSHA = Occupational Safety and Health Administration CLP = Classification, Labeling and Packaging Regulation

STOT = Specific Target Organ Toxicity

LD<sub>50</sub> = Median Lethal Dose

DNEL = Derived No Effect Level

ACGIH = American Conference of Governmental Industrial Hygienists

TSCA = Toxic Substances Control Act (USA)
DSL = Domestic Substances List (Canada)

AICS = Australian Inventory of Chemical Substances

Revision Date: July 17, 2023

**Revision Number:** 1 **Supersedes:** NA

Other: New Zealand, Australia

Indication of Changes: No changes.

Written in accordance with the provisions of OSHA 1910.1200 App D (2012) and Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 including New Zealand and Australia specific information. (GHS format)

The information and recommendations contained herein are believed to be reliable. However, the supplier makes no warranties, express or implied, concerning the use of this product. The buyer must determine conditions of safe usage and assumes all risk and liability in handling this product.