

Earth Trailing Lead Reels

20m - Earth Trailing Lead Reel

Part No. Various

Developed with Australian utilities the Earth Reel has a 1000V insulated handle covering a strong stainless steel rod to eliminate a requirement in some regions to cover the spike. The tapered stake assists with easy driving into the variety of soil densities encountered in the field. Incorporated into the earth reel is a custom brass bushing running the full width of the reel, this runs smoothly on the stainless steel shaft ensuring continuous reliable continuity.

Features

- 20m Insulated Earth Trailing Lead
- 1000V Insulated Handle
- Green flexible 1.0mm Cable 0.6/1kV
- Adjustable drag system w/out tools
- Option for direct connection via 4mm Banana plug
- Brass Bushing for extra Low Resistance Connectivity
- Stackable Banana Plug for multiple connections at service end
- Stainless steel construction

Part No.	Stake Length	Stake Type	Lead Length (m)	Weight
ETL20SS	225	Spike	20	1.1
ETL20SSL	645	Spike	20	1.2



ETL20SSL

ETL20SS

50m - Earth Trailing Lead Reel

Part No. ETL50

The 50M Earth Trailing Lead is a high quality portable cable reel supplied with 50 metres of flexible cable 1.5mm 30/0.25. Furthermore it features only Quality Components. Earth Trailing Lead Connects directly to most brands of test equipment. Equipped with One alligator clip and two 4mm banana plugs. It is also supplied with a temporary independent earth stake. The cable is calibrated and resistance is marked on the Trailing Lead.

• The Earth Trailing Lead is also available in 100M Version.



60m - Earth Trailing Lead Reel

Part No. 2010-083

- Lightweight reels
- Large comfortable handle
- Sits on the ground or any flat surface
- Clips on reel to retain earth spikes/pins
- Clips on reel to retain the end of test leads
- Ability to daisy chain allows extra long length in manageable chunks.
- The manageable chunks make reels lighter and easier to carry, helping to quickly resolve any connectivity issues