



Reel Jacks™ Drum Stand - iTOOLco

Part No. RJ6K

iTOOLco's Reel Jacks™ make cable pulls run smooth and easy. These innovative drum jack stands have four sealed bearings that capture the axle to prevent the drum from traveling during the pull.

Features

- Closed head traps axle preventing it from falling out or traveling horizontally
- Separate sides allow the jacks to be used safely on uneven ground
- Easily folded for storage and transportation
- Can be used with 560 to 1675mm drums
- Easy to carry at 16kg per side
- For use with iTOOLco Axles - see below "Axle Specs" for details
- Set up in less than 1 minute
- Four bearings make wire pulling smooth and easy
- No drills or extra tools required



Supplied as a set of 2



CLICK or SCAN for Reel Jack Stand Video

SCAN OR CLICK TO VIEW VIDEO

Capacity
2.7 Tonne - RJ6K-AX02
1.3 Tonne - RJ6K



Separate Stands and height adjustment allows for use on uneven ground

Real Jacks™ Stand Specifications

Part No.	Description	Spindle	WLL (kg)	Min/Max Drum Diameter (mm)	Dimensions per side (mm)	Wt per Set (kg)
RJ6K-AX02*	Reel Jack Drum Stand	AX02	2700	560 to 1675	940L x 254W 290H (Folded) 978H (Assembled)	32 (Without Axle)
RJ6K		AX08	1300			

*RJ6K-AX02 Includes axles AX02 & AX08

Hand Crank

top mounted for easier lift & leveling while not interfering with the arbor position, axle or drum

4 Sealed Bearings

makes cable pulling smooth & easy

Adjustable Handle

ergonomically designed for even balance

Pull Pin
locks in place for safer operations

Folds down Compact
easy to carry and transport

T-Base Footprint
can't tip over. separate side are safer on uneven ground



Axle connection



Reel Jacks™ Axle Specification

Part No.	AX08	AX02	AXS01 (Solid)
Capacity (T)	1.36	2.7	0.907
Weight (kg)	9	20.4	16.3
Dimensions (mm)	1016L x 41OD	1829L x 70OD	1829L x 30.5OD
Availability	Included (RJ6K)	Included (RJ6K-AX02)	Sold Separately

*RJ6K-AX02 Includes axles AX02 & AX08