



Mechanical Dynamometers - Nagaki (NGK)

Part No: AS Series

Trust only the Original - Established in 1946

Used to measure tension in wires, belts and cables, the NGK tension meter features two pulling eyes, connected to an analog indicator. This allows the user to accurately monitor tension and adjust equipment and loads accordingly.

NGK Dynamometers are lightweight, compact and plated to resist corrosion. All models feature a large face dial for easy reading of measurements.

- Made in Japan from Japanese components
- Precise measurement of tension and loads
- Kilogram/force (kN) dial display
- Accuracy ±3%
- Plated to resist corrosion
- Leather Storage case included
- Supplied with In-Service Date sticker





	Dent Ma	Capacity (kN/T)	Increments) (N)	Attachments	Dimensions (mm)			Wt
	Part No.				Α	В	С	(kg)
Table Dimensions	AS-3	3/0.3	50	Eye-Clevis	110	65	16	0.7
	AS-10L	10/1	200	Eye-Eye**	135	65	28	1.2
	AS-20L	20/2	500	Eye-Eye**	135	65	28	1.6
	AS-30	30/3	500	Eye-Eye	150	80	28	2.0
	AS-50	50/5	1000	Eye-Eye	260	95	28	3.0
	AS-100	100/10	2000	Eye-Eye	360	100	38	7.2

**1 & 2 Tonne versions also available with Eye-Clevis attachments. Use Part No's AS-10 & AS-20

QLD/NT 07 3212 8999 VIC 03 9793 1622 TAS/SA 0499 996 441 WA 08 9455 5574 NSW/ACT 0417 631 443 ©The Energy Network 2023