



Arc-Rated Outer Gloves - Youngstown

LV Gloves - Outers - 8.6 Cal Arc Rated

The FR 4000 is a seamless coated palm style work glove that is both cut resistant and flame resistant. This glove will not drip, melt or ignite if exposed to sparks or flames. Designed and built in a manner to offer excellent dexterity allowing workers to handle the smallest items while still being highly protected from various hazards. Features a nitrile based blended coated palm that maintains grip even in oily conditions.

- Cut Resistant: Level A7 (ANSI/ISEA)
- Puncture Resistant: Level 4 (ANSI/ISEA)
- Arc Rating: 8.6 Cal/cm2
- Flame Resistant: Exceeds Industry Standards According to ASTM D6413
- Palm: No Drip No Melt Textured Coating



Part No.	Material	Length (mm)	Sizes Available
YT12-4000-60-*	Nitrate	305 (12")	*S, M, L, XL, XXL & 3XL

*Add size suffix when ordering (e.g. 12-4000-60-M)

LV Gloves - Outers - 25 Cal Arc Rated

The Arc Rated 255mm (10") Leather Protector is ergonomically designed to fit perfectly over Class 0 and 00 rubber insulating gloves per ASTM F496/ASTM F696. Manufactured with the highest quality goat grain leather along with an innovative glove pattern to create a leather protector with unrivaled fit and dexterity.

This glove features an FR Strap System to ensure that nothing on this protector will drip, melt or ignite if exposed to an arc flash.

- Puncture Resistant: Level 3 (ANSI/ISEA)
- Arc Rating: 25 Cal/cm2
- FR Strap: Woven Webbing with DuPont™ Kevlar®
- FR Fastener: Heat Stabilized Heavy Duty Hardware
- Leather: 0.6-0.9mm Goat Grain



Part No.	Material	Length (mm)	Sizes Available
YT16-4100-10-*	Goat	255 (10")	*7, 8-8.5, 9-9.5, 10-10.5, 11 & 12

*Add size suffix when ordering (e.g. 16-4100-10-9-9.5)

HV Gloves - Outers - 32 Cal Arc Rated

The Arc Rated 305mm (12") Primary Leather Protector is ergonomically designed to fit perfectly over Class 1 through 4 rubber insulating gloves per ASTM F496/ASTM F696. Manufactured using premium cow grain along with an innovative glove pattern to create a leather protector with unrivaled fit and dexterity.

This model features a cow suede cuff and FR Strap System to ensure that nothing on this protector will drip, melt or ignite if exposed to an arc flash.

- Puncture Resistant: Level 5 (ANSI/ISEA)
- Arc Rating: 32 Cal/cm2
- FR Strap: Woven Webbing with DuPont™ Kevlar®
- FR Fastener: Heat Stabilized Heavy Duty Hardware
- Leather: 1.0mm+ Cow Grain
- Cuff Leather: 1.2mm+ Cow Suede



Part No.	Material	Length (mm)	Sizes Available
YT16-5100-12-*	Leather	305 (12")	*7, 8-8.5, 9-9.5, 10-10.5, 11 & 12

*Add size suffix when ordering (e.g. 16-5200-12-9-9.5)



ARC
Rated



25 CAL
ARC Rated



32 CAL
ARC Rated