




Adjustable Chain Oiler


THE ONLY 62" (1.6m) LONG REACH CHAINSAW AVAILABLE

Insulated section length

Available in 3 Lengths



Foam Filled



Tree Trimming Solutions

Chain Saw, Long Reach - Foam Filled

Part No. REL-LR-Series

Reliable's REL-LR-62-TEN-A long reach hydraulic chainsaw are intended for safely cutting and trimming trees from the ground or an aerial bucket. The powerful hydraulic drive motor can easily make cuts up to 330mm in diameter. With an overall length of 1600mm (Also available 1900 & 2250mm), the operator may easily reach areas not possible with a standard chain saw.

Features include a trigger guard and safety trigger to prevent accidental movement of the chain, a covered sprocket guard, and a rubber collar hand stop. A quick set spool can be turned 180 degree for closed center/open center operations.

Features

- Powerful hydraulic drive motor
- EZ selector valve allows change between open and closed centre without tools
- Foam filled fibreglass shaft to prevent ingress of moisture and provide additional electrical safety protection
- Trigger guard, sprocket guard, rubber hand guard and scabbard
- Flush face couplers fitted

Technical Data

Part No.	REL-LR-62-TEN-A	REL-LR-75-TEN-A	REL-LR-88-TEN-A
OAL (mm)	1600	1900	2250
Insulated Section (mm)	845	1175	1515
Cut Capacity (mm)	330		
System	Open or Closed		
Flow Range (lpm)	19-30		
Operating Pressure (PSI)	(1,000-2,000) 68.9-137.8 Bar		
Pressure Port Thread	9/16" -18 SAE O-Ring		
Return Port Thread	3/4" -16 SAE O-Ring		
Chain Pitch (mm)	8.25/25.4		
Chain Gauge (mm)	1.47/25.4		
Plastic Scabbard	SCAB-PS		
Weight (kg)	3.6	4.3	5

Foam Filled to Eliminate Moisture Ingress



Low Pressure Hydraulic Hoses - Twin-Line - NRP Jones

- Twin low pressure flexible hydraulic hose
- Strain relief sleeve over crimped connections
- Temperature: -4°C to 93°C
- Certified non-conductive rubber
- Flush face couplers both ends
- Neoprene inner tube with nitrile outer, reinforced two textile braid



Part No.	Length (m)	ID (mm)	OD (mm)	Rated Pressure (PSI)	Min Burst (PSI)	Min Bend (mm)	Weight (kg)
B098-FF	3	3/8	3/4	2250	9000	127	1.9



Tree Trimming Kit in protective bag (included)



Open the bag and you have choice of tree trimming tools in the length required, all in a convenient heavy-duty vinyl tool bag that offers maximum protection for the tools

Rope Insulator

Part No. Various Sizes



Rope Insulator not included in Tree Trimming kits



Scratch proof Markings!

Tree Trimming Kits - Hastings

Part No. 4141 & 4142

- For line clearance crews, trouble shooting and emergency call outs
- Complete kit with sticks, cutter, saw and adaptors in Protective carry bag
- Tested to ASTM F-711, IEC 60855 & OSHA
- Refer to local network provider procedures for live line use

Part No	Stick OD (mm)	Length of Sections (m)	Maximum Height (m)	Description	Weight (kg)
4141	32	1.2	4.8	Tree Trimming Kit (Refer below for contents list)	6.8
4142	32	1.8	7.2		8.6

Part No.	Item Description	Qty in Kits	
		4141	4142
546-4	Stick Sectional Extension 1.2m	4	-
546-6	Stick Sectional Extension 1.8m	-	4
4125	Cutter - Tree Pruner 600mm FG	1	1
A18007	Base Cap 32mm Female	1	1
A10012	Adaptor Male Universal 32mm	1	1
P10046	Universal "S" Hook	1	1
A11000	Universal Pruning Saw	1	1
A10016	Universal Saw Handle	1	1
A30007	Pruning Saw Scabbard	1	1
TENM305	Bag Tree Trim to suit 1.2m	1	-
TENM315	Bag Tree Trim to suit 1.8m	-	1

Spare parts & accessories available contact TEN

- For insulating ropes used around energised lines
- Add one to you Tree Trimming Kit
- Blank fibreglass middle section with eyes each end

Part No	Fibreglass Length (mm)
4010	1100
4004-1	305
4005	860

Triangular Telescopic Measuring & Operating Sticks

Part No. MV Series

- Dislodge and remove branches from the ground
- Accepts all universal tree trimming tools (saws, pruners etc)
- Replaceable sections, no disassembly tools required
- Fluoro lime green tip section is foam filled
- Tested to ASTM F711 & OSHA
- Stick includes double sided Universal Disconnect Hook #P10431-2
- Markings will not chip, peel or rub off

Triangular Profile = NO Twist



Storage Bag



Part No.	Stick c/w Quick release head	Extended Length (m)	Retracted Length (m)	Base OD (mm)	Wt (kg)	Add "K" for Storage Bag
MV-25	MV-25-Q	7.8	1.6	48.5	3.7	TENM301
MV-30	MV-30-Q	9.2	1.7	52.5	4.5	
MV-35	MV-35-Q	10.6	1.7	56.0	5.5	
MV-40	MV-40-Q	12.0	1.8	60.4	6.5	



Quality Tools, Equipment & Line Materials for the Energy Industry.

Tree Trimming Equipment & Adaptors



Part No.	10-019	A11002	A11004	A10033
Description	Tree Pruning Head Insulated with Rope	Tree Pruning Head	Replacement Head	Replacement Rope Pulley
Details	Drop Forged Steel Blades cut to 38mm Ø. 300mm Fibreglass Shaft – Twin Pulley with 7.6m Polyprop Rope and Universal Head	Drop Forged Steel Blades cut to 38mm Ø. Single Pulley with Universal Head	Drop Forged Steel Blades cut to 38mm Ø	Cast Aluminium Pulley
Weight (kg)	1.3	0.88	0.79	0.11



Part No.	A11000	P11004	A30007	A11000-K
Description	Universal Pruning Saw	Replacement Blade	Saw Scabbard	Universal Pruning Saw & Scabbard
Details	Teflon Coated Fast Cutting. Curved Blade 400mm long with 7 Teeth per 25mm and Universal Head	Teflon Coated Fast Cutting. Curved Blade 400mm long with 7 Teeth per 25mm	For Safe Storage of # A11000 Saw, Heavy Duty Stitching	Kit Includes A11000 + A30007
Weight (kg)	0.36	0.14	0.45	0.79



Part No.	P10032	A10016	10-106	P10046
Description	Pruning Saw Casting	Saw Handle	Universal Spiral Hook	Universal "S" Hook
Details	Aluminium Casting replacement for A11000	Handle for # A11000 Saw, Cast Aluminium with Wingnut	Used for Grabbing/Holding Branches/Wires	Used for Lifting Overhead Wires
Weight (kg)	0.22	0.22	0.34	0.10

Debri Removal Tool - MADI

Part No. DV-1

- Universal aluminium base for strong secure fit and corrosion resistance
- Two-prong angled tapered design for quick vegetation removal in tight spaces
- Can also be used to remove tree limbs and break ice

