

1 Pump - Multiple Heads

High Pressure Drive Unit

Part No AHP700L

- Compact and lightweight design for mobile field application
- Suitable for operating single acting crimping/cutting/punching tools of 700 bar/10,000PSI

6.4kg with 2 batteries



Cutting



7.7kg

105mm Armoured Cutting Head
Part No SDG105C



4.3kg

85mm Armoured Cutting Head
Part No SDG852C



3.8kg

45mm Armoured Cutting Head
Part No SDG45C



5.2kg

85mm Cutting Head ACSR/ Steel
Part No SDK85C



2kg

Cutting Head
Part No SDK20P33MC

Crimping



100T Crimping Head
Part No PK1000C
33kg with dies



25T Crimping Head
Part No PK252C
5.3kg



12T Crimping Head
Part No PK12042FPC
4.5kg

Multi Tools



3.5kg

Multi Head Crimping/Cutting/Punching
Part No PK120UNVC

40mm Cutting Die
Part No UCACSR



12T Die Adaptor
Part No UA12T

Punch Adaptor
Part No UA12P



Highly Versatile





105mm Armoured Cutting Head Part No SDG105C

- Cuts copper and aluminium cables (for armoured cables)
- 120kN cutting force for extremely wide cutting range up to 105mm diameter
- Closed cutting head with bolt interlock, under no pressure, rotates 360°, with quick coupling
- Compact design permits cutting also in constricted places



85mm Armoured Cutting Head Part No SDG852C

- Hydraulic cutting head 85mm diameter
- High user safety through cutting head with bolt interlock
- Exceptionally light and compact design
- Cuts copper and aluminium cables with light weight steel armouring (depending on cable type)
- Closed cutting head with bolt interlock, under no pressure, rotates 360°, with quick coupling



45mm Armoured Cutting Head Part No SDG45C

- Hydraulic cutting head 45mm diameter
- High cutting force cuts armoured copper, aluminium cables and ACSR
- Also suitable for round material made of Al, Cu and Steel
- Closed head with bolt interlock, flip open jaws
- Cutting head with quick coupling, under no pressure, rotates 360°



85mm Cutting Head ACSR/ Steel Part No SDK85C

- Hydraulic cutting head 85mm diameter
- Cuts copper and aluminium cables with light weight steel armouring (depending on cable type)
- Suitable for fine stranded cable and telecommunication cable
- Safe working due to high ground stability by double stops
- Open cutting head with quick coupling, under no pressure, rotates 360°
- Uniform cut by knife guide



Cutting Head Part No SDK20P33MC

- Hydraulic cutting head up to 20mm diameter
- Cuts ACSR, copper and aluminium cables with reinforcement, tension cables and soft round steel
- Two sickle-shaped blades to cut cables



100T Crimping Head Part No PK1000C

- 100T Hydraulic crimping head up to 1600mm²
- Compact, simple design with extreme crimping force
- Quick coupling



25T Crimping Head Part No PK252C

- 25T Hydraulic crimping head 16 - 625mm²
- Crimping head with quick coupling, under no pressure, rotates 360°



12T Crimping Head Part No PK12042FPC

- 12T Hydraulic crimping head 10 - 400mm²
- C-head with large 42mm opening width
- Up to 60% less crimping operations due to wide crimping compared with 6T tools
- Crimping head with quick coupling, under no pressure, rotates 360°



Multi Head-Crimping/Cutting/Punching Part No PK120UNVC

- Hydraulic universal head
- **One head for crimping, cutting and punching - one tool for all**
- For field operations where all common jobs can be carried out with just one tool
- Universal head with quick coupling, under no pressure, rotates 360°, flip top style
- Various cutting dies for aluminium and copper conductors with and without armouring, as well as ACSR



40mm Cutting Die Part No UCACSR

- Cutting die for Al/Cu conductors to max. 40mm diameter with and without armouring
- For ACSR conductors to DIN EN 50182 and high-tensile steel cables
- In conjunction with EKM60UNVL the cutting range is up to 25mm diameter



12T Die Adaptor Part No UA12T

- Adaptor for crimping dies



Punch Adaptor Part No UA12P

- Hole punch adaptor
- UA6P - can be used with 6 Ton tools
- UA12P - can be used with 12 Ton tools