



Remote Cutting Heads

Klauke Remote Hydraulic Cutting Heads



7.7kg

105mm Armoured Cutting Head
Part No **SDG105C**

Part No: SDG105C

- Cuts copper and aluminium cables (for armoured cables)
- 120 kN cutting force for extremely wide cutting range up to 105mmOD
- Exceptionally light and compact design
- Closed cutting head with bolt interlock, under no pressure, rotates 360°, with quick coupling
- Compact design permits cutting also in constricted places
- Handle enables easy handling
- For connecting to hydraulic pumps with 700 bar operating pressure for best possible cutting results

Cutting range	max. 105mmOD
Cutting force	120 kN
Operating pressure	max. 700 bar
Length	432 mm
Weight	7.7 kg



4.3kg

85mm Armoured Cutting Head
Part No **SDG852C**

Part No: SDG852C

- High user safety through cutting head with bolt interlock
- Exceptionally light and compact design
- Cuts copper and aluminium cables with light weight steel armouring (depending on cable type)
- Closed cutting head with bolt interlock, flip top style, under no pressure, rotates 360°, with quick coupling
- For connecting to hydraulic drive units with 700 bar operating pressure for the best possible cutting results
- Handle enables easy handling

Cutting range	max. 85mmOD
Cutting force	60 kN
Operating pressure	max. 700 bar
Length	445 mm
Weight	4.3 kg



3.8kg

45mm Armoured Cutting Head
Part No **SDG45C**

Part No: SDG45C

- High cutting force cuts armoured Cu and Al cables, and Al/St cables (ACSR)
- Also suitable for round material made of Al, Cu and Steel
- Extremely robust design and lightweight
- Closed head with bolt interlock, flip open jaws
- Cutting head with quick coupling, under no pressure, rotates 360°
- For connecting to hydraulic pumps with 700 bar operating pressure for best possible cutting results

Cutting range	max. 45mmOD
Cutting force	60 kN
Operating pressure	max. 700 bar
Length	340 mm
Weight	3.8 kg

