



Height Safety Equipment

HEIGHT SAFETY EQUIPMENT

Fall Arrestor



1011742

Part No	Length	Weight
1011742	10m	5kg

- Unique side payout reduces entry guide and cable wear
- No annual factory re-certification lowers costs and downtime
- Load indicating hook identifies unit removal from service
- 4.5mm x 10m galvanised steel cable, 1200daN min break, 17mm opening

Manyard, Energy Absorbing Lanyard



M1010024

- Contracts from 1.8m to 1.2m to reduce tripping, snagging or dragging
- Specially woven shock absorbing inner core reduces fall forces
- No energy absorber "pack" makes it more comfortable to use
- Heavy duty tubular outer sleeve serves as a back up lanyard
- Unique warning flag provides visual proof of a sustained fall
- Grid label allows easy recording of inspection dates

Part No	Length	Hooks	Weight
M1010024	2m	2 x 19mm	1kg

Lanyard, Stretchstop with Energy Absorber



L11SEC1.5

- Elastic inner core contains the unextended length of webbing
- Integral compact energy absorber
- Outer load bearing tubular polyester webbing gives strength and durability
- Available in a variety of lengths and hook options

Part No	Length	Hooks	Webbing	Weight
L11SEC1.5	1.5m	2 x 19mm	Single	0.5kg

Safety Tie Off



ME10091.6

- Quick and easy set up of temporary anchorage
- 1m strap with dee ring one end and reversed eye the other
- Protective sleeve prevents webbing wear

Part No	Length	Hooks	Weight
ME10091.6	1m	Dee Ring/ Reversed Eye	0.5kg

Pole Straps



136.1S

- Fitted with an adjuster to easily adjust working length
- Protective sleeve lengthens life of webbing
- Double acting 19mm opening hooks at each end
- 138.1S-SP features 1 x double action hook, 1 x triple action karabiner

Part No	Length	Weight
136.1S	1.8m	3kg
138.1S-SP	2.4m	3kg
138.1S	2.4m	3kg
139.1S	2.7m	3kg

Karabiner



91326

- Triple acting with 14mm opening, Captive D, Forged Steel
- Rated to 30kN

