



SALES • SERVICE • MANUFACTURE • HIRE

Foam Duct Sealant



One Polywater FST-MINI cartridge seals approximately TEN x 25mm ducts

BENEFITS

• Strong:

Holds up to 7m of water head pressure

Compatible:

PVC, HDPE, Rigid Steel, EMT, Fibreglass, and Cable Jackets

• Easy:

Two-part foam is mixed in nozzle as it is injected into duct

Quick:

Foam expands and cures quickly even when water is present

• Multi-Use:

Packages are resealable

98% closed Cell content



Polywater FST™ MINI Foam Duct Sealant for Conduit Sizes 20 to 50mm

Effectively Seals Small Conduits and Innerducts

Polywater® FSTTM MINI is an expanding, quick-setting, "closed-cell" foam that is injected into a conduit to provide a watertight seal. The seal is superior to pliable duct putties and "open-cell" aerosol canned foams.

Recommended for small conduits (less than 40 mm)

Part No	Description
FST-MINI	1 x 50ml FST Cartridge 2 x Mixing Nozzles 6 x Foam Discs 1 x Pair of gloves 1 x Instructions
FST-MINI-1G	FST-MINI + 1 x Application Tool (TOOL-50-11)
TOOL-50-11	Application Tool

FEATURES

- FST Duct Sealant [™] has 98% closed-cell content for increased strength and resiliency
- FST Duct Sealant TM resists seven meters of waterhead pressure
- FST Duct Sealant [™] is compatibile with cable and duct materials
- FST Duct Sealant [™] is chemically resistant to gasoline, oils, dilute acids and bases, and most unsaturated hydrocarbons
- Prevents the passage of gas; does not sag; will not dry out; and is re-enterable



Positioning the Conductors



Foam strip inserted



Insert nozzle past the first dam

