



Honeywell SALISBURY



HV Leather Outers - Next Generation - Salisbury

Part No. NGILP3S-Size

Next Generation Leather Protectors are manufactured from top grade cowhide and goatskin leather. Protectors are crafted using heavy duty 4ply cotton thread and are equipped with a non-metallic buckle for a secure fit.

The Next Generation Leather Protector is designed exclusively for the insulated Electriflex™ rubber gloves. These new leather protectors offer utility workers the comfort and dexterity needed to get the job done. The redesigned leather protector was constructed to help amplify the flexibility of the Electriflex™ gloves.

Features

- 305mm (12") overall Length
- Flame-resistant against burns, cuts, abrasions & punctures
- Made from specially-tanned goatskin for optimum dexterity & wear
- Comes with pull strap & buckle
- Buckle is non-metallic
- Straight cuff
- Meets ASTM F696
- Sizes 8, 8.5, 9, 9.5, 10, 10.5, 11, 12

Sizing

| Part No. | Size |
|-------------|--------|
| NGILP3S-8 | 8 |
| NGILP3S-8H | 8 1/2 |
| NGILP3S-9 | 9 |
| NGILP3S-9H | 9 1/2 |
| NGILP3S-10 | 10 |
| NGILP3S-10H | 10 1/2 |
| NGILP3S-11 | 11 |
| NGILP3S-12 | 12 |

Specifications

| | | |
|---------------------|------------------------|----------------------|
| Hand material | Goatskin Leather | 1.00 - 1.6 thickness |
| Cuff Material | Cowhide suede leather | 1.2 - 1.78 thickness |
| Draw-strap Material | Nylon | |
| Threading | Cotton thread 16, 4ply | |
| Length | 305mm | |
| Weight | 230g | |

Contact TEN for additional LV & HV Leather Outer Gloves styles

LV & HV Leather - Outers - Salisbury

- Glove protectors offer excellent comfort and protection
- Feature adjustable straps with non-metallic buckles and are stitched with polyester thread for strong seams
- Manufactured from imported goatskin
- All Salisbury Leather Protectors meet ASTM F696 standards
- 355mm available on request (ILPG5S-*)

| Part No. | Voltage | Sizes | Length (mm) |
|-----------|---------|----------------|-------------|
| ILPG10A-* | LV | 7-12 Dual Size | 250 |
| ILPG3S-* | HV | 7-12 Dual Size | 300 |

*Add size suffix when ordering

ILPG10A



ILPG3S