



## Hastings Remote Cutters

### Universal Cutter

**Part No. 10-019**

This versatile tool cuts branches up to 38mmOD and conductor up to 50mm<sup>2</sup> (AL/CU)

- Drop Forged Steel Blades cuts up to 38mm Ø.
- 300mm Fibreglass Shaft and capture hook
- Twin Pulleys with 7.6m of Poly-Rope
- Universal tool Head

**Ideal for cutting away Lightning Arrester leads**



Part No.	Description	Cuts	Jaw Opening (mm)	Wt (kg)
10-019	Universal Cutter with 7.6m Poly Rope	Up to 50mm <sup>2</sup> Al & Cu	38mm	1.3

### Emergency Wire Cutters

**Part No. 4186**

Ideal for your "MAKE SAFE" emergency crew

- Universal head with fibreglass insulating shaft & conductor capture hook
- Long lever arm and double pulley reduces pulling requirement on rope
- Shear drop forged cutter blade

Part No.	Description	Cuts	Max Cable OD (mm)	Wt (kg)
4186	Universal Cutter with 7.6m Poly Rope	ACSR/Al/Cu	14.3	2.1

**Available as a KIT - CREATE YOUR OWN or select one of our standard kits**

### Emergency Wire Cutting Kit

**Part No. 4186-K**

- Designed for emergency cutting of lines or conductors
- Ideal for cutting away Lightning Arrester leads
- Cutting head attaches to standard universal head operating stick

Part No.	Item Description	Qty
4186	Cutter with Universal Head, Cuts up to 14mm OD ACSR, 28mm OD Al/Cu	1
4010	Insulator for Rope with 1100mm of Fibreglass and Eyes each end	1
TENM413	Carry Bag for above	1

### Tree Trimming Kit

**Part No. 4141 & 4142**

Open the bag and you have choice of tree trimming tools in the length required, all in a convenient heavy-duty vinyl tool bag that offers maximum protection for the tools

- For line clearance crews, trouble shooting and emergency call outs
- Complete kit with sticks, cutter, saw and adaptors in Protective carry bag
- Tested to ASTM F-711, IEC 60855 & OSHA
- Refer to local network provider procedures for live line use

Part No	Stick OD (mm)	Length of Sections (m)	Maximum Height (m)	Description	Weight (kg)
4141	32	1.2	4.8	Tree Trimming Kit (Contact TEN for contents list)	6.8
4142	32	1.8	7.2		8.6

