



Quality Tools, Equipment & Line Materials for the Energy Industry.



ORDER FORM - Portable Earthing Device

All details are required for quotation, please enter data where requested or circle sections

Network Properties - Enter Value


Maximum Fault Current (kA) /0.5 Sec
Indicate kA rating

Maximum Voltage (kV)
For stick length purposes

PED Assembly Type

PED Configuration						
Description	3 Phase with separate down-lead	3 Phase with centre attached down-lead	3 Phase trifurcating plate with attached down-lead	Down-lead only, Single	3 Phase linked down-lead	2 Phase, Jumper earth

Cable Type & Length Required



Type of Cable Aluminium Copper

1. Phase to Phase 2. Phase to Phase 3. Phase to Ground

Length of Cable (m)

Please remember to nominate slightly longer cable length than what is required to allow the earth clamp to be easily secured, but do not to add excess, as this can cause cable to flick out with force and cause injury to workers under unexpected fault condition.

Phase/Conductor Clamps to suit (Enter a value)

 Circular (mm) <table border="1"> <tr><td>Min OD</td><td><input type="text"/></td></tr> <tr><td>Max OD</td><td><input type="text"/></td></tr> </table>	Min OD	<input type="text"/>	Max OD	<input type="text"/>	 Flat Busbar (mm) <table border="1"> <tr><td>Min OD</td><td><input type="text"/></td></tr> <tr><td>Max OD</td><td><input type="text"/></td></tr> </table>	Min OD	<input type="text"/>	Max OD	<input type="text"/>	 Fixed Ball Joint OD of Ball (mm) <table border="1"> <tr><td>20</td><td>25</td></tr> <tr><td>Other</td><td><input type="text"/></td></tr> </table>	20	25	Other	<input type="text"/>
Min OD	<input type="text"/>													
Max OD	<input type="text"/>													
Min OD	<input type="text"/>													
Max OD	<input type="text"/>													
20	25													
Other	<input type="text"/>													

Phase/Conductor Clamp Fitting

Snap On Shotgun Screw Up Bayonet Screw Up Fixed Stick * "T" Handle
 *Reference Chart over HEX Screw Up Taplin Screw Up *Stick Length (m) Handle

Download/Earth Tail Clamp

 Circular (mm) <table border="1"> <tr><td>Min OD</td><td><input type="text"/></td></tr> <tr><td>Max OD</td><td><input type="text"/></td></tr> </table>	Min OD	<input type="text"/>	Max OD	<input type="text"/>	 Flat Busbar (mm) <table border="1"> <tr><td>Min OD</td><td><input type="text"/></td></tr> <tr><td>Max OD</td><td><input type="text"/></td></tr> </table>	Min OD	<input type="text"/>	Max OD	<input type="text"/>	 Fixed Ball Joint OD of Ball (mm) <table border="1"> <tr><td>20</td><td>25</td></tr> <tr><td>Other</td><td><input type="text"/></td></tr> </table>	20	25	Other	<input type="text"/>
Min OD	<input type="text"/>													
Max OD	<input type="text"/>													
Min OD	<input type="text"/>													
Max OD	<input type="text"/>													
20	25													
Other	<input type="text"/>													

Download/Earth Tail Fitting

Snap On Shotgun Screw Up Bayonet Screw Up Fixed Stick * "T" Handle
 *Reference Chart over HEX Screw Up Taplin Screw Up *Stick Length (m) Handle

Customer Contact Details

Name: _____ Company: _____
 Address: _____
 Phone No.: _____ Email: _____

PED Protective Bag

Advise your specs or TEN can recommend a suitable bag



Please email this form to sales@tengroup.com.au











Quality Tools, Equipment & Line Materials for the Energy Industry.







ORDER FORM - Reference Chart

Phase Clamps: Please Note: Other clamps available

	Rated to 25kA /0.5 sec Suitable for - Circular - 3 to 33mm - Snap-On		Rated to 45kA /0.5 sec Suitable for - Circular & Flat - 5 to 40mm		Rated to 45kA /0.5 sec Suitable for - Circular & Flat - 5 to 40mm		Rated to 45kA /0.5 sec Suitable for - Circular & Flat - 5 to 40mm
MT-613/3		MT-815-E*		MT-815-C*		MT-815-S*	
	Rated to 10kA /0.5 sec Suitable for - Circular - 10 to 30mm - Snap-On		Rated to 45kA /0.5 sec Suitable for - Circular - 16 to 85mm		Rated to 45kA /0.5 sec Suitable for - Circular & Flat - 10 to 25mm		Rated to 45kA /0.5 sec Suitable for - Circular - 12 to 48mm - Snap-On
MT-612		MT-736-085		MT-1921-E*		MT-701	

Swap the end fitting by changing the *PREFIX on the Part No., as indicated above - **C** = Hex - **E** = Bayonet - **S** = Shotgun - **EH** = Handle


Earth Clamps: Please Note: Other clamps available

	Rated to 16kA /0.5 sec Suitable for - Circular & Flat - 0 to 25mm		Rated to 30kA /0.5 sec Suitable for - Circular & Flat - 0 to 35mm		Rated to 25kA /0.5 sec Suitable for - Flat - 0 to 13mm		Rated to 25kA /0.5 sec Suitable for - Circular & Flat - 0 to 25mm - Lockable
MT-840/1		MT-843		MT-847		MT-870	

Fixed Points:

		
25mmOD Ball - M12 Threaded hole or rod - 24mm Hex base		
MT-3951-1	MT-3951	MT-3950/35

Brass Stubs:





	Rating kA /0.5 sec	Bolt Size	Stub OD (mm)	Stub Length (mm)
M12/22 BRS STUB	25	M12	25	60
M12/25 BRS STUB	25	M12	25	60
M16/22 BRS STUB	45	M16	25	60
M16/25 BRS STUB	45	M16	25	60

Fixed Earthing

Earthing Stubs

Temporary Earth Rod Driver

PED Application Accessories:

			
Clamp removal adaptor	Clamp removal adaptor	Application platform	Application platform
CRA-C	HEX	CRA-K	SUNRISE
MT-630-K	SUNRISE	MT-630-C	HEX

Stick Accessories:

Stick/s	Min Height	Max Height	Ask TEN to recomend a Kit	
Stick Type	Universal	Shotgun	Bayonet	Hex
Adaptors	Shotgun	Bayonet	Snap On	Line Clamp